# capella<sup>®</sup> 60 corner pure air<sup>®</sup> II bath

capella means "chapel" in Italian. and like the chapel—a place of reverence, contemplation—the capella® pure air® II bath is a tranquil retreat.



The Capella's  $^{\mbox{\tiny \$}}$  unique corner configuration allows for roomy relaxation.

#### features:

- Exclusive 360° Balanced Airflow™ system
- 600 watt variable speed heated air blower
- Thermal Lumbar Comfort<sup>™</sup> (TLC)
- Timed purge cycle
- Safely use salts and aromatic oils
- PrO<sub>3</sub><sup>™</sup> Ozone Sanitation System standard

## capella® 60 pure air® II bath

model number: BE60

exterior dimensions: 60" long x 60" wide x 201/2" high

interior dimensions: 50" long x 34" wide(mid)

operating gallons: **73 gallons** 



**Detail:** The Capella<sup>®</sup> Pure Air<sup>®</sup> II bath features integral neck and backrests, and Jacuzzi's exclusive TLC system.





# Capella<sup>®</sup> 60" Corner Pure Air II<sup>™</sup> Bath


## **Ordering Information**

Product Code: BE60 Capella® 60" Corner Pure Air II™ Bath Right Hand


- Center Drain Location
- Accessories / Hardware: Trim Kit Rotary: #BN21
  Trim Kit Finishes Available: (827) - Chrome (898) - Brushed Chrome (815) - Satin Nickel (829) - Bright Brass (805) - Platinum

(826) - Brushed Nickel

(845) - Oil Rubbed Bronze



Product Shown: Capella® 60" Pure Air II™ Bath Right Hand Shown Model: BE60 \* Measurements inside unit represent cutout in floor to allow for drain/overflow. Minimum Service Access dimensions given.



## Installation Notes

Refer to installation instructions included with fixture before beginning installation. Please confirm product availability and specifications before commencing with any installation work.

PRODUCT SPECIFICATIONS AND AVAILABILITY ARE SUBJECT TO CHANGE WITHOUT NOTICE.

# **Technical Specifications**

**Dimensions** 60° L x 60° W x 20-1/2° H (1524 mm) L x (1524 mm) W x (521 mm) H

Drain/Overflow A: 18" (457 mm) B: 12-1/8" (308 mm)

**Cutout** See Illustration Below

**Total Weight** 1197 lb (543 kg) / 55.8 lb/sq. ft. (272 kg/m<sup>2</sup>)

## **Operating Gallonage**

73 U.S. Gal. (276 Liters), Min. 55 U.S. Gal. (208 Liters) Max. 90 U.S. Gal. (341 Liters)

Product Weight 150 lb (80 kg)


Skirt Mounting Optional

## **Electrical Specifications**

Requires a dedicated GFCI protected separate circuit. Blower: 120 VAC, 15 AMP, 60 Hz.

#### Heater

No water heater is available on this unit. Blower has integral air heater.



#FQ86 12/06